The GT (Sub ASME / ISO) range comprises sealless magnet drive end suction centrifugal pumps for general chemical transfer applications.



# GT (SUB ASME / ISO)



For general transfer duties, the **GT** pump has been specifically designed as a compact, costeffective and minimum maintenance pump. The GT is sized below ASME / ISO dimensions and has a number of features, which make it one of the most highly competitive pumps in its class. Thanks to its simplicity of maintenance, space-saving design and interchangeability, the GT pump proves a very popular choice.


GT pumps are of a close coupled construction and can be supplied free standing or baseplate mounted. Prime mover specifications of all denominations can be catered for with a range of Synchronous Magnet Drives rated to match.

		60Hz	50Hz
	Heads	10 to 190ft	2 to 41m
	Flows	4 to 163gpm	1 to 30m3/hr
	Max Power	15 hp	11 KW
	Temp Range	-40 to 500°F	-40 to 260°C
	Number of Stages	1	
	Max Case Working Pressure	275 psi	18.9 bar
	Max Suction Pressure	275psi (18.9 bar)	
	Differential Head	190 ft	58 m
	Standard Delivery	Stock to 4 weeks	
	Speed Range	1,450 to 3,500rpm	
	Materials of Construction	316 SS, Alloy 20, Alloy B2	
	Bearing Materials Available	Alfa sintered SiC	
	Hydrotest Pressure	412 psi	28 bar
	Max Viscosity	200 cSt	
	Solids Range	Maximum of 5% w/w less than	150 microns
	Motor Details	Industry standard	


### **APPLICATIONS**

Ideal for a wide range of general transfer applications within the chemical, pharmaceutical and refining industries.

## CONSTRUCTION



### PERFORMANCE



# Visit our website at: www.sundyne.com